

Analog IP Cell

Two Stage 12 bit SAR ADC

ADC12b – XFAB XH018



General Description

This cell is a ratiometric operating and very fast 12 bit SAR ADC comprising of a two stages. The first stage converts one bit in advance which is used for digital error correction. The supply voltage is used as reference. The conversion time is about 3.5µs @ 12 MHz in continuous mode.

Ratings, Parameters and Conditions

Absolute Maximum Ratings						
Parameter / Condition	Symbol	Min	Typ	Max	Unit	Comment
Operating Temperature	T _{OP}	-40		120	°C	
Supply Voltage	V _{DD}	-0.3		3.6	V	
Input Voltage	V _{IN}	-0.3		V _{DD} +0.7	V	
Output Voltage	V _{OUT}	-0.3		V _{DD} +0.7	V	

Electrical Parameters						
Parameter / Condition	Symbol	Min	Typ	Max	Unit	Comment
Operating Temperature	T _{OP}	-40		85	°C	
Supply Voltage	V _{DD}	2.7	3.0	3.3	V	
Current Consumption	I _{DD}		0.8	1	mA	12 MHz operation
Clock Frequency	f _{CLK}	1	12	16	MHz	
Conversion Cycle	N _{CYC}		40		Clocks	
Int. Reference Voltage	V _{REF}		V _{DD30} / 2		V	
Resolution	RES		V _{DD30} / 4096		V	
Differential Nonlinearity	DNL	-1.5		+1.5	LSB	
Integral Nonlinearity	INL	-2.5		+2.5	LSB	
Input Voltage	V _{IN}	0		V _{DD30}	V	
Startup Time	T _{SU}			50	µs	

Interface and Symbol

IO-Description			
Interface	I/O	Function	Comment
IBN5U	input	bias current input	~5uA
VIN	input	input voltage	
CLK	input	clock frequency	
ENABLE	input	enable	
DATA	output	data out	
SOC	input	start of conversion	
EOC	output	end of conversion	
SCE	input	scan path enable	low if unused
SCI	input	scan path in	low if unused
SCO	output	scan path out	
VDD30, VSS	power	supply voltage	

